



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - France

SAFETY DATA SHEET

LEVISCRYL RS 700 BASE WHITE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : LEVISCRYL RS 700 BASE WHITE

1.2 Relevant identified uses of the substance or mixture and uses advised against

| Identified uses |
|----------------------|
| Consumer use |
| Uses advised against |
| None |

Product use : Waterborne coating for exterior use.

1.3 Details of the supplier of the safety data sheet

Akzo Nobel Decorative Paints France
Département : Levis
Z.I. "Les Bas Prés"
C.S. 70113
60761 Montataire Cedex
France
N° Téléphone : 03.44.64.91.00
N° Télécopie : 03.44.64.91.90
www.levispeintures.com

e-mail address of person responsible for this SDS : fds.fr@akzonobel.com

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : Numéro ORFILA (INRS) : + 33 (0)1 45 42 59 59

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General : P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.

Prevention : P273 - Avoid release to the environment.

Response : Not applicable.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national or international regulations.

Supplemental label elements : Contains 1,2-benzisothiazol-3(2H)-one, CMIT/MIT(3:1) and octhilinone (ISO). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

SECTION 3: Composition/information on ingredients

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|--|---|-----------|--|--|---------|
| titanium dioxide | REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7 | ≥10 - ≤15 | Carc. 2, H351 (inhalation) | - | [1] [*] |
| 3-iodo-2-propynyl butylcarbamate | EC: 259-627-5 CAS: 55406-53-6 | <0.1 | Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | ATE [Oral] = 500 mg/kg ATE [Inhalation (dusts and mists)] = 0.5 mg/l M [Acute] = 10 M [Chronic] = 1 | [1] |
| 1,2-benzisothiazol-3(2H)-one | REACH #: 01-2120761540-60 EC: 220-120-9 CAS: 2634-33-5 | <0.05 | Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 | ATE [Oral] = 500 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1 | [1] |
| 3-(4-isopropylphenyl)-1,1-dimethylurea | EC: 251-835-4 CAS: 34123-59-6 Index: 006-044-00-7 | ≤0.1 | Carc. 2, H351 STOT RE 2, H373 (blood) Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | M [Acute] = 10 M [Chronic] = 10 | [1] |
| CMIT/MIT(3:1) | REACH #: 01-2120764691-48 EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5 | <0.0015 | Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 | ATE [Oral] = 100 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Corr. 1C, H314: C ≥ 0.6% Skin Irrit. 2, H315: 0.06% ≤ C < 0.6% Eye Dam. 1, H318: C ≥ 0.6% Eye Irrit. 2, H319: 0.06% ≤ C < 0.6% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100 | [1] |
| 2-octyl-2H-isothiazol-3-one | EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5 | <0.001 | Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 | ATE [Oral] = 125 mg/kg ATE [Dermal] = 311 mg/kg ATE [Inhalation (dusts and mists)] | [1] |

SECTION 3: Composition/information on ingredients

| | | | | | |
|--|--|--|--|---|--|
| | | | Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 See Section 16 for the full text of the H statements declared above. | = 0.27 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100 | |
|--|--|--|--|---|--|

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a physical, health or environmental hazard
[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.
Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if easy to do. Get medical attention if irritation occurs.
- Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
- Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact : No specific data.
- Inhalation : No specific data.
- Skin contact : No specific data.
- Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

SECTION 5: Firefighting measures

| | |
|---|---|
| Hazards from the substance or mixture | : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
| Hazardous combustion products | : Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides |
| 5.3 Advice for firefighters | |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents. |

SECTION 6: Accidental release measures

| | |
|--|---|
| 6.1 Personal precautions, protective equipment and emergency procedures | |
| For non-emergency personnel | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. |
| For emergency responders | : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| 6.2 Environmental precautions | |
| | : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. |
| 6.3 Methods and materials for containment and cleaning up | |
| Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| Large spill | : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. |
| 6.4 Reference to other sections | : See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information. |

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

- Protective measures**
- : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene**
- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Ensure spraying away from persons. Avoid inhalation of vapor, spray or mist. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations**
- : Not available.
- Industrial sector specific solutions**
- : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

- Recommended monitoring procedures**
- : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

SECTION 8: Exposure controls/personal protection

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|----------------------------------|------|-----------------------|--------------------|--------------------|----------|
| titanium dioxide | DNEL | Long term Inhalation | 28 µg/m³ | General population | Local |
| | DNEL | Long term Inhalation | 170 µg/m³ | Workers | Local |
| 3-iodo-2-propynyl butylcarbamate | DNEL | Long term Inhalation | 0.023 mg/m³ | Workers | Systemic |
| | DNEL | Short term Inhalation | 0.07 mg/m³ | Workers | Systemic |
| | DNEL | Short term Inhalation | 1.16 mg/m³ | Workers | Local |
| | DNEL | Long term Inhalation | 1.16 mg/m³ | Workers | Local |
| | DNEL | Long term Dermal | 2 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Dermal | 0.345 mg/kg bw/day | General population | Systemic |
| 1,2-benzisothiazol-3(2H)-one | DNEL | Long term Dermal | 0.966 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 1.2 mg/m³ | General population | Systemic |
| | DNEL | Long term Inhalation | 6.81 mg/m³ | Workers | Systemic |
| | DNEL | Long term Inhalation | 0.02 mg/m³ | General population | Local |
| CMIT/MIT(3:1) | DNEL | Long term Inhalation | 0.02 mg/m³ | Workers | Local |
| | DNEL | Short term Inhalation | 0.04 mg/m³ | General population | Local |
| | DNEL | Short term Inhalation | 0.04 mg/m³ | Workers | Local |
| | DNEL | Long term Oral | 0.09 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Oral | 0.11 mg/kg bw/day | General population | Systemic |
| | | | | | |

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

SECTION 8: Exposure controls/personal protection

| | |
|---------------------------------|--|
| Hand protection | <p>: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.</p> <p>When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm.</p> <p>Gloves should be replaced regularly and if there is any sign of damage to the glove material.</p> <p>The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.</p> <p>The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.</p> |
| Body protection | <p>: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</p> |
| Other skin protection | <p>: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</p> |
| Respiratory protection | <p>: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Wear a respirator conforming to EN140 with type A/P2 filter or better. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.</p> |
| Environmental exposure controls | <p>: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.</p> |

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

| | |
|---|-------------------|
| Physical state | : Liquid. |
| Color | : White. |
| Odor | : Characteristic. |
| Odor threshold | : Not available. |
| Melting point/freezing point | : Not available. |
| Boiling point, initial boiling point, and boiling range | : 100°C (212°F) |
| Flammability | : Not available. |

SECTION 9: Physical and chemical properties

| | |
|---------------------------------|--|
| Lower and upper explosion limit | : Not available. |
| Flash point | : Not available. |
| Auto-ignition temperature | : Not available. |
| Decomposition temperature | : Not available. |
| pH | : 8 [Conc. (% w/w): 100%] [DIN EN 1262] |
| Viscosity | : Kinematic (room temperature): 1074 mm ² /s [DIN EN ISO 3219] Kinematic (40°C): Not applicable. [DIN EN ISO 3219] |
| Solubility(ies) | : |

| Media | Result |
|------------|-------------------------|
| cold water | Soluble [OECD (TG 105)] |

| | |
|---|-------------------|
| Partition coefficient: n-octanol/ water | : Not applicable. |
| Vapor pressure | : Not available. |
| Relative density | : 1.49 |
| Vapor density | : Not available. |
| Particle characteristics | |
| Median particle size | : Not applicable. |
| Percentage of particles with aerodynamic diameter ≤ 10 µm | : 0 |

9.2 Other information

| | |
|------------------------------|-------------------|
| Minimum ignition energy (mJ) | : Not available. |
| Fundamental burning velocity | : Not applicable. |
| SADT | : Not available. |
| Heat of combustion | : Not available. |
| Aerosol product | |
| Type of aerosol | : Not applicable. |

SECTION 10: Stability and reactivity

| | |
|---|--|
| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
| 10.2 Chemical stability | : The product is stable. |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| 10.4 Conditions to avoid | : No specific data. |
| 10.5 Incompatible materials | : No specific data. |
| 10.6 Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|-------------|---------|------------|----------|
| 3-iodo-2-propynyl butylcarbamate 1,2-benzisothiazol-3(2H)-one | LD50 Oral | Rat | 1470 mg/kg | - |
| | LD50 Oral | Mouse | 1150 mg/kg | - |
| | LD50 Oral | Rat | 1020 mg/kg | - |
| 2-octyl-2H-isothiazol-3-one | LD50 Dermal | Rabbit | 690 mg/kg | - |
| | LD50 Oral | Rat | 550 mg/kg | - |

Conclusion/Summary : Not available.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|----------------------------------|--------------|----------------|--------------------------|----------------------------|-------------------------------------|
| 3-iodo-2-propynyl butylcarbamate | 500 | N/A | N/A | N/A | 0.5 |
| 1,2-benzisothiazol-3(2H)-one | 500 | N/A | N/A | N/A | 0.05 |
| CMIT/MIT(3:1) | 100 | 50 | N/A | N/A | 0.05 |
| 2-octyl-2H-isothiazol-3-one | 125 | 311 | N/A | N/A | 0.27 |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-----------------------------|------------------------|---------|-------|----------|-------------|
| 2-octyl-2H-isothiazol-3-one | Eyes - Severe irritant | Rabbit | - | 100 mg | - |

Conclusion/Summary : Not available.

Sensitization

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|--|------------|-------------------|-----------------|
| 3-iodo-2-propynyl butylcarbamate | Category 1 | - | larynx blood |
| 3-(4-isopropylphenyl)-1,1-dimethylurea | Category 2 | - | |

Aspiration hazard

Not available.

SECTION 11: Toxicological information

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact : No known significant effects or critical hazards.
- Inhalation : No known significant effects or critical hazards.
- Skin contact : No known significant effects or critical hazards.
- Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact : No specific data.
- Inhalation : No specific data.
- Skin contact : No specific data.
- Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects : Not available.
- Potential delayed effects : Not available.

Long term exposure

- Potential immediate effects : Not available.
- Potential delayed effects : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary : Not available.
- General : No known significant effects or critical hazards.
- Carcinogenicity : No known significant effects or critical hazards.
- Mutagenicity : No known significant effects or critical hazards.
- Reproductive toxicity : No known significant effects or critical hazards.

- 11.2 Information on other hazards
 - 11.2.1 Endocrine disrupting properties
 - Not available.
 - 11.2.2 Other information
 - No additional information.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

SECTION 12: Ecological information

| Product/ingredient name | Result | Species | Exposure |
|----------------------------------|--------------------------------------|---|----------|
| titanium dioxide | Acute LC50 15.9 mg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute LC50 >1000 mg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| | Acute EC50 956 ppb Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute EC50 0.16 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 500 ppb Fresh water | Crustaceans - Hyalella azteca | 48 hours |
| | Acute LC50 2920 ppb Marine water | Crustaceans - Neomysis mercedis - Adult | 48 hours |
| | Acute LC50 40 ppb Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 95 ppb Marine water | Fish - Oncorhynchus kisutch - Juvenile (Fledgling, Hatchling, Weanling) | 96 hours |
| | Acute LC50 100 ppb Fresh water | Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling) | 96 hours |
| | Acute LC50 72 ppb Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| 3-iodo-2-propynyl butylcarbamate | Acute LC50 67 ppb Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| | Acute LC50 67 µg/l Fresh water | Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling) | 96 hours |
| | Chronic NOEC 8.4 ppb | Fish - Pimephales promelas | 35 days |
| | Acute EC50 97 ppb Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute EC50 2.24 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute EC50 3.7 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute EC50 1.1 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute EC50 2 ppm Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 10 to 20 mg/l Fresh water | Crustaceans - Ceriodaphnia dubia | 48 hours |
| | Acute LC50 540 ppb Fresh water | Fish - Lepomis macrochirus | 96 hours |
| 1,2-benzisothiazol-3(2H)-one | Acute LC50 167 ppb Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| | Acute LC50 0.75 ppm Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| | Acute LC50 1.8 ppm Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| | Acute LC50 1.6 ppm Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| | Acute EC10 0.000224 mg/l | Algae - Navicula peliculosa | 48 hours |
| | Acute EC50 0.084 mg/l | Algae - Desmodesmus subspicatus | 72 hours |
| | Acute EC50 0.00129 mg/l | Algae - Navicula peliculosa | 48 hours |
| | Acute EC50 0.42 mg/l | Daphnia | 48 hours |
| | Acute EC50 107 ppb Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute EC50 180 ppb Fresh water | Daphnia - Daphnia magna | 48 hours |
| 2-octyl-2H-isothiazol-3-one | Acute EC50 320 ppb Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 154 ppb Fresh water | Fish - Notemigonus crysoleucas | 96 hours |
| | Acute LC50 47 ppb Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| | Acute LC50 50 ppb Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| | Acute LC50 65.5 ppb Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| | Acute LC50 140 ppb Fresh water | Fish - Pimephales promelas | 96 hours |
| | Chronic NOEC 8.5 ppb | Fish - Pimephales promelas | 35 days |
| | | | |
| | | | |
| | | | |

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

SECTION 12: Ecological information

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|--|--------------------|-----|-----------|
| 3-(4-isopropylphenyl)-1,1-dimethylurea | 2.87 | - | low |
| 2-octyl-2H-isothiazol-3-one | 2.45 | - | low |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Disposal considerations : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

| Waste code | Waste designation |
|--------------|--|
| EWC 08 01 12 | waste paint and varnish other than those mentioned in 08 01 11 |

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

SECTION 13: Disposal considerations

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | IMDG |
|---------------------------------|----------------|----------------|
| 14.1 UN number or ID number | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - |
| 14.3 Transport hazard class(es) | - | - |
| 14.4 Packing group | - | - |
| 14.5 Environmental hazards | No. | No. |

14.6 Special precautions for user : **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

VOC for Ready-for-Use Mixture : Not available.

SECTION 15: Regulatory information

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Fire point

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

| Product/ingredient name | List name | Name on list | Classification | Notes |
|-------------------------|-------------------------------------|--|----------------|-------|
| titanium dioxide | France Occupational Exposure Limits | titane (dioxyde de) en Ti; dioxyde de titane | Carc. C2 | - |

Biocidal products regulation

Active substances

| Ingredient name |
|--|
| 3-iodo-2-propynyl butylcarbamate 1,2-benzisothiazol-3(2H)-one 3-(4-isopropylphenyl)-1,1-dimethylurea terbutryn bronopol CMIT/MIT(3:1) 2-octyl-2H-isothiazol-3-one pyrithione zinc |

Reinforced medical surveillance : Decree n ° 2012-135 of January 30, 2012 relating to the organization of occupational medicine: not applicable

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

SECTION 15: Regulatory information

15.2 Chemical Safety Assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|-------------------------|--------------------|
| Aquatic Chronic 3, H412 | Calculation method |

Full text of abbreviated H statements

| | |
|--------|--|
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H310 | Fatal in contact with skin. |
| H311 | Toxic in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H330 | Fatal if inhaled. |
| H331 | Toxic if inhaled. |
| H351 | Suspected of causing cancer. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH071 | Corrosive to the respiratory tract. |

Full text of classifications [CLP/GHS]

| | |
|-------------------|---|
| Acute Tox. 2 | ACUTE TOXICITY - Category 2 |
| Acute Tox. 3 | ACUTE TOXICITY - Category 3 |
| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
| Aquatic Acute 1 | AQUATIC HAZARD (ACUTE) - Category 1 |
| Aquatic Chronic 1 | AQUATIC HAZARD (LONG-TERM) - Category 1 |
| Aquatic Chronic 2 | AQUATIC HAZARD (LONG-TERM) - Category 2 |
| Aquatic Chronic 3 | AQUATIC HAZARD (LONG-TERM) - Category 3 |
| Carc. 2 | CARCINOGENICITY - Category 2 |
| Eye Dam. 1 | SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 |
| Skin Corr. 1 | SKIN CORROSION/IRRITATION - Category 1 |
| Skin Corr. 1C | SKIN CORROSION/IRRITATION - Category 1C |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| Skin Sens. 1 | SKIN SENSITIZATION - Category 1 |

SECTION 16: Other information

| | |
|----------------------------|---|
| Skin Sens. 1A STOT RE 1 | SKIN SENSITIZATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 |
| STOT RE 2 | SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 |

Date of printing : 15-11-2024
Date of issue/ Date of revision : 22-10-2024
Date of previous issue : 28-1-2024
Version : 2
Unique ID : DA7DF488320C1EEEEAF86D29DC83A018E

Notice to reader

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.